

PVC BRANDA TEKNİK BİLGİ FORMU

PVC TARPAULIN TECHNICAL DATA SHEET- HS: 392190600012



TS 257 EN 20811
Certificate No: I 1710162045

ÜRÜN TANIMI : PRODUCT DESCRIPTION :	HI-TECH PANAMA PVC BRANDA HI-TECH PANAMA TRUCK TARPAULIN		
TEKNİK ÖZELLİKLER TECHNICAL SPECIFICATIONS	STANDARTLAR STANDARDS	BİRİM UNIT	DEĞER VALUE
ANA KUMAŞ : BASE FABRIC :	DIN 60 001		100% PES
İPLİK TÜRÜ : YARN TYPE :	DIN EN ISO 2060	POLYESTER	3300 DTX
DOKUMA SIKLIĞI : WEAVING CONSTRUCTION :			9X9 (23X23)
BİRİM ALAN KÜTLESİ : WEIGHT :	TS 1534 EN ISO 2286-2 DIN EN ISO 2286-2	gr/m ² gr/m ²	1250 ± 5
GENİŞLİK : WIDTH :		cm cm	150-250-300-320 (MÜŞTERİ İSTEĞİNE BAĞLI) (DEPENDS ON CLIENTS REQUEST)
RULO UZUNLUĞU : ROLL LENGTH :		m m	50-250 (MÜŞTERİ İSTEĞİNE BAĞLI) (DEPENDS ON CLIENTS REQUEST)
ÜRÜN ÇEŞİTLİLİĞİ : SURFACE TREATMENT :			PARLAK-MAT-DESENLİ GLOSSY-MATT-EMBOSS
SICAKLIK DİRENCİ : TEMPERATURE RESISTANT :	DIN EN 1876-1	°C	-30
SICAKLIK DİRENCİ : TEMPERATURE RESISTANT :	IVK/Pkt.5	°C	+70
KOPMA DİRENCİ (çözgü/atkı) : TENSILE STRENGTH (warp/weft):	TS 2008 EN ISO 1421 EN ISO 1421	N/5cm	6500 / 5800
YIRTILMA DİRENCİ (çözgü/atkı) : TEAR STRENGTH (warp/weft):	TS EN ISO 4674-1 EN ISO 4674-1	N	1100 / 1100
YAPIŞMA : ADHESION :	TS EN ISO 2411 EN ISO 2411	N/5cm	130
RENK HASLIĞI : COLOUR FASTNESS :	BS EN ISO 105-BO2		6+
YANMAZLIK : FLAMMABILITY (FR) :	DIN 4102-1B2 / NF P 92-507		B2 / M2/B1 (TALEP EDİLİRSE) (IF DEMANDED)

ATTENTION! The above Technical Data has an arithmetical average deviation ratio as +/- 5%.



PVC KAPLAMA
PVC COATED



SU GEÇİRMEZ
WATERPROOF



ULTRAVİOLE
ULTRAVIOLET



Selda MUTLU
R & D Executive

Erol ÇEBİ
Production Manager

Ali EROL
Export & Import Manager

Mehmet KAYA
General Manager